

panel	style	TFT-LCD
	Resolution	Max. : 1920X1200
	Interface	single/dual LVDS
	Voltage	5V, 12V
PC-RGB	Mode	DOS, VGA, SVGA, XGA, SXGA+, UXGA, WXGA, WXGA+, WSXGA, UXGA
	Range of horiz sync	30-75KHz
	Range of field sync	56-75Hz
	Display color	16777216
	MAX mode	1920X1200@60Hz
Input signal	TV	Color system: PAL /SECAM/NTSC (optional)system
		Sounds system: B/G, D/K, I, M, N, L/L'
		Frequency range: 48.25MHz—863.25MHz
	AV/ S-Video/	Color system: PAL/NTSC/SECAM system
		AV signal: CVBS/1.0Vp-p@75ohm
		S-VIDEO: Y: 1Vp-p@75ohm /C: 0.286Vp-p@75ohm
	RGB	sync: horiz and field separation, TTL, positive or negative
		Signal amplitude: 0.7Vp-p@75ohm
HDMI	Support format: 480i/P、576i/P、720P、1080i/P	
	Compatible standard: HDMI 1.3 /HDCP 1.2	
Audio	Signal amplitude: 500mV rms	
Output signal	Video	Signal amplitude: CVBS 1.0Vp-p
	Audio	Power rate: 3W*2
		socket: 4Pin/2.54mm interval
Control button	Common seven keys: power/input selection/menu/channel+/channel-/volume+/volume-	
OSD menu:	brightness, contrast, auto correction, horiz field position, function setting, color system, language, background, noisy reduction	
OSD language(optional):	Chinese, English, Spanish, French, Portuguese, Russian, etc	
Power input:	Internal large power: 5Vstb、12V、5V 、5V/12V (optional)	
	Circumscribed Adapter: 12Vdc	
size:	233.5mm(L) × 67.5mm(W) × 18mm(H)	

Plug and paly: support

