



Cat NB2 Module















Product Description

The SIM7022 is Multi-Band NB-IoT module solution in a SMT type .

It has strong extension capability with rich interfaces including UART, GPIO etc. The module provides much flexibility and ease of integration for customer's application.

The package of SIM7022 is compatible with SIM800C and SIM7020. This also maximizes the investments of customers, and enables a short time-to-market. It is designed for applications that need low latency, Low throughput data communication in a variety of radio propagation conditions. Due to the unique combination of performance, security and flexibility, this module is ideally suited for M2M applications, such as metering, asset tracking, remote monitoring, E-health etc..

Key Benefits

- With Power Save Mode(PSM) and Extended
 Discontinuous Reception(eDRX), SIM7022 can extend
 battery life to 10 years
- SIM7022 provides deeper coverage enhancement compared to GSM
- The package of SIM7022 mostly are compatible with SIM800C and SIM7020.

Smart machine Smart decision



General Features

LTE-FDD:

B1/B2/B3/B4/B5/B8/B12/B13/B14/B17/B18/B 19/B20/B25/B26/B28/B66/B70/B85

Control Via AT Commands Supply voltage range: 2.2V-4.3V

Operation temperature: -40°C to +85°C Dimensions: 17.6 X 15.7 X 2.3mm

Weight: $1.3g \pm 0.2g$

Data

Uplink: 159Kbps Downlink: 127Kbps

SMS

Text and PDU mode

Consumption

0.8 uA @ PSM 0.11 mA @ Idle(DRX=2.56s) 0.018 mA @ Idle(eDRX=163.84s; PTW=25.6s)

Other Features

Firmware update via UART
TCP/UDP/HTTP(s)/TLS/SSL/DTLS*/DNS/NTP*/
PING*/PPP*/LwM2M/COAP/MQTT(s)/FOTA

Interfaces

UART
USIM card (1.8V/3V)
Netlight
RI
Reset
ADC
GPIO

WARKUP

Certifications

RoHS/REACH/RCM/CE/FCC/GCF/Deutsche Telekom/Telefonica/TIM/Vodafone*/UKCA

Smart machine Smart decision

^{*} means under developing/on-going/planning